

Securing Cargo Worldwide

## Fortris Load Secure (UK) Ltd.

Unit 18 Cinder Road Burntwood. Staffordshire. **WS7 3FS** 

Tel: 01543 677 256

Email: sales@fortrisuk.co.uk

Website: www.fortrisuk.co.uk

## **BXT3-16 Battery Powered Strapping Tool**

The latest generation of BXT tools have been designed in collaboration with some of the most demanding manufacturing plants across Europe, ensuring that the BXT3 strapping hand tool consistently offers industry leading performance.

The innovative integrated touch screen allows users to easily change tool settings to suit their specific requirements whilst the display also provides an indication of the tension force being applied as well as strap cycle completion.



Strapping Tool	BXT3-16
Operation Mode	Auto / Semi / Manual
Tension Range Standard	900 - 2,500N
Tension Range Soft	400 - 1,360N
Variable Tension Speed	0 - 220mm/s
Tool Weight(Incl. Battery)	3.8kg
Dimensions (L x W x H)	370 x 141 x 135mm
Working Temperature	-10°C to +40°C
Relative Humidity	Up to 90%
Battery / Charger	
Charger Type	Bosch
Battery Charger Voltage	100 or 110 or 230V
Charging Time	15-30 Minutes
Battery Type	Bosch Li-lon 18V, 2.0Ah
Cycles Per Charge Low Tension	800
Cycles Per Charge Medium Tension	400
Cycles Per Charge High Tension	200
Strap	
Material	Polyester (PET) or Polypropylene (PP)
Width	12-13mm, 15-16mm
Thickness	0.5 - 1.0mm

## Features:

- 0 Tension Welding
- Favourite Strapping **Function**
- Strap Alignment Indication
- Strap Dust Blow Out Vent
- Battery Protection
- · Real Time Indication of Applied Tension
- Display Colour Indication for **Tool Status Information**

Full Touch **User Interface** 



Variable Tension



Favourite Strapping Strap Alignment Function



Indicator

